


# Circular Hollow Section

## AS 1163



Designation		Weight
Size	Thickness	
<i>OD</i>	<i>T</i>	<i>M</i>
mm	mm	Kg/m
21.3	2.0	0.952
21.3	2.6	1.200
21.3	3.2	1.430
26.9	2.0	1.230
26.9	2.3	1.400
26.9	2.6	1.560
26.9	3.2	1.870
33.7	2.0	1.560
33.7	2.6	1.990
33.7	3.2	1.870
33.7	4.0	2.930
42.4	2.0	1.990
42.4	2.6	2.550
42.4	3.2	3.090
42.4	4.0	3.790
48.3	2.3	2.610
48.3	2.9	3.250
48.3	3.2	3.560
48.3	4.0	4.370
48.3	5.4	5.710
60.3	2.3	3.290
60.3	2.9	4.110
60.3	3.6	5.030
60.3	4.5	6.190
60.3	5.4	7.310
76.1	2.3	4.190
76.1	2.6	4.710
76.1	3.2	5.750
76.1	3.6	6.440
76.1	4.5	7.950
76.1	5.9	10.200
88.9	2.6	5.530
88.9	3.2	6.760
88.9	4.0	8.380
88.9	5.0	10.300
88.9	5.9	12.100

Designation		Weight
Size	Thickness	
<i>OD</i>	<i>T</i>	<i>M</i>
mm	mm	Kg/m
101.6	2.6	6.350
101.6	3.2	7.770
101.6	4.0	9.630
101.6	5.0	11.900
114.3	3.2	8.770
114.3	3.6	9.830
114.3	4.5	12.200
114.3	5.4	14.500
139.7	3.0	10.100
139.7	3.5	11.800
139.7	5.0	16.600
139.7	5.4	21.300
165.1	3.5	13.900
165.1	5.0	19.700
165.1	5.4	21.300
168.3	4.8	19.400
168.3	6.4	25.600
168.3	7.1	28.200
219.1	4.8	25.400
219.1	6.4	33.600
219.1	8.2	42.600
273.1	4.8	31.800
273.1	6.4	42.100
273.1	9.3	60.500
273.1	12.7	81.600
323.9	6.4	50.100
323.9	9.5	73.700
323.9	12.7	97.500
355.6	6.4	55.100
355.6	9.5	81.100
355.6	12.7	107.000
406.4	6.4	63.100
406.4	9.5	93.000
406.4	12.7	123.000
457.0	6.4	71.100
457.0	9.5	105.000
457.0	12.7	139.000